



August 31, 2004

STANDARDS BULLETIN 2004-09

Amendment to Standard

Second Edition of CAN/ULC-S705.1-01 (Including Amendment 1)

**STANDARD FOR THERMAL INSULATION –
SPRAY APPLIED RIGID
POLYURETHANE FOAM, MEDIUM DENSITY –
MATERIAL - SPECIFICATION**

ULC is pleased to announce the release of Amendment 1 to the Second Edition of CAN/ULC-S705.1-01, Standard for Thermal Insulation - Spray Applied Rigid Polyurethane Foam, Medium Density, Material - Specification. Amendment 1 has been approved by the ULC Committee on Thermal Insulation Materials and Systems, and has been published with the date of August 2004, while the Second Edition of this Standard was published in July 2001.

CAN/ULC-S705.1-01 will be of interest to builders, architects and anyone involved in the construction or renovation of building structures. This Standard has been developed for the assessment of volatile organic compound emissions from polyurethane foam used in residential buildings. The Standard specifies recommended procedures for the use of test chambers to evaluate emissions from the insulation product at a point in time following its installation. This Standard is to be used in conjunction with CAN/ULC-S705.2, Thermal Insulation - Spray Applied Rigid Polyurethane Foam, Medium Density, Application – Specification.

Amendment one contains revisions to Clauses 5.2.1, 5.2.2, 5.3.1, 5.4.1 and additional clause number 5.2.3. Additionally, a note has been added to Subsection 5.4

Should you require any additional information, please contact Robert Long at 613-755-2729 Ext. 6227 or email: Robert.Long@ca.ul.com

The amended Standard can be ordered for \$150.00 through our website at www.ulc.ca and selecting ULC Online Store. Once at the ULC Online Store select "Standards".

Yours truly,

UNDERWRITERS' LABORATORIES OF CANADA

G. Rae Dulmage
Director, Standards Department

