

April 13, 2005

STANDARDS BULLETIN 2005-11

Second Edition of CAN/ULC-S705.2-05

STANDARD FOR THERMAL INSULATION – SPRAY APPLIED RIGID POLYURETHANE FOAM, MEDIUM DENSITY – APPLICATION

ULC is pleased to announce the publication of the Second Edition of CAN/ULC-S705.2-05, Standard for Thermal Insulation – Spray Applied Rigid Polyurethane Foam, Medium Density – Application. This Standard has been approved by the ULC Committee on Thermal Insulation Materials and Systems, and has been published with the date of February 2005.

This Standard outlines requirements for the installation of spray applied rigid polyurethane foam, medium density. The material can be installed as thermal insulation, air barrier, vapour barrier or any combination of these three applications. This Standard may be used for non-building applications when agreed to by the supplier and the purchaser. Spray application of spray polyurethane foam, medium density according to this Standard requires the use of materials and/or equipment that could be hazardous.


A Certification Bulletin will be released providing further information regarding this Standard. The Certification Bulletin will also specify the effective date for any requirements.

If you require any additional information, please contact Robert Long at 613-755-2729 Ext. 6227 or email: <mailto:Robert.Long@ca.ul.com>

This standard can be ordered for \$150.00 through our website at www.ulc.ca and selecting ULC Online Store. Once at the ULC Online Store select "New Standards Publications." After 30 days from the date of this letter the standard can be found by selecting "Standards".

Yours truly,

UNDERWRITERS' LABORATORIES OF CANADA



G. Rae Dulmage
Director, Standards Department
Standards Department and Government Relations Office
200-440 Laurier Avenue West
Ottawa, Ontario
K1R 6X7

